

**Item no.****93155-25****Self-tapping screw 5.5 x 20-25, sealing washer Ø 16 mm**

Drilling capacity steel..... 0.5 mm - 2.0 mm

Drilling capacity aluminum..... 0.5 mm - 2.0 mm

Packaging unit (PU)..... 100 pieces

93160-25**Self-tapping screw 6.0 x 25-25, sealing washer Ø 16 mm**

Drilling capacity steel..... 0.4 mm - 2.0 mm

Drilling capacity aluminum..... 0.5 mm - 2.0 mm

Packaging unit (PU)..... 100 pieces

93161-25**PREMIUM Self-tapping screw 6.0 x 25, sealing washer Ø 16 mm**

Drilling capacity steel.....0.5 mm - 1.5 mm

Drilling capacity aluminum.....0.4 mm - 2.0 mm

Packaging unit (PU).....100 pieces

**93155-26****Beware of
metal swarf
on the roof!****Self-drilling screw 5.5 x 25, sealing washer Ø 16 mm**

Drilling capacity steel..... 0.4 mm - 1.5 mm

Drilling capacity aluminum..... 0.4 mm - 5.0 mm

Packaging unit (PU)..... 100 pieces

**93148-20****Self-drilling screw 4.8 x 20 for Internal Connector RAIL**

Drilling capacity steel..... 0.5 mm - 3.0 mm

Drilling capacity aluminum..... 0.7 mm - 4.0 mm

Packaging unit (PU)..... 100 pieces

Technical Data

Material Stainless steel, EPDM rubber seals

Design Tool SL-Rack-Configurator **Solar.Pro.Tool**.

Statik The structural analysis is carried out in accordance with the current country-specific standards (EN 1991, EC1 for Germany). Depending on snow loads, wind loads, or when utilizing large modules, it may be necessary to use more than the usual 4 fastening points. Make sure to observe the installation manual of the respective module manufacturer. The load-bearing capacity of the roof has not been evaluated by SL Rack.

Your opinion is important to us!

It is our top priority to make the installation process for you as quick, easy and efficient as possible. Please share your experiences, ideas or criticism with us, so we can continue to improve our products and develop new ones.



SL Rack **Feedback**
[Provide Feedback >](#)



SL Rack **Website**
[Check it out >](#)



SL Rack **YouTube**
[Watch videos >](#)

Find us on



Subject to technical
changes and misprints.
Version 01/2023 V3