





# Innovative Product Development

"Our racking systems have been developed since 1996 and are continuously optimized. Pre-assembled components that are quick and easy to install, prompt order processing, a reliable product supply and cost-effectiveness are our focus.

All our components follow a convenient top-down installation approach, ensuring a smooth and timesaving workflow. SL Rack systems are installer-friendly, intuitive and standardized, while still having the flexibility to adapt to each respective project site."

Sincerely,



Ludwig Schletter





**26**...... Years of experience

**30**...... GW installed worldwide

15..... Product specialists are happy to support you

**EU**..... Almost exclusively manufactured in Germany and Europe

100% ..... Aluminum and stainless steel- extremly durable



Visit our website: <u>www.sl-rack.com</u>




Check out our
YouTube-channel:
Installation videos >

<sup>\*</sup>Our warranty conditions apply. They are available at www.sl-rack.com



For a successful carport project it is crucial to start with an individual design by our technicians. Are you interested in a unique or innovative design? Reach out to us! Our knowledgeable team is happy to quickly respond and guide you through the process.



- » Carports for residences, company parking lots, public parking lots, etc.
- » Complete modular system (easily adjusts to project- and customer-specific requirements)
- » Competent advice, calculations and support
- » Works with any standard module sizes
- » 5°- 15° inclination



- » C1 One-sided parking (East/West/ South orientation possible)
- » **C1S** One-sided sun protection
- » **C1R** One-sided rain protection



Carport variant with sun protection



Carport variant with rain protection







- » C2 Double-sided parking (East/ West/South orientation possible)
- » **C2S** Double-sided sun protection
- » C2R Double-sided rain protection



Carport variant with sun protection



Carport variant with rain protection







- » C2Y Y-version, double-sided parking (East/West)
- » C2YS Y-version, double-sided sun protection
- » C2YR Y-version, double-sided rain protection



Carport variant with sun protection



Carport variant with rain protection





## **SCOPE OF DELIVERY**

The carport racking is delivered as a complete set, ready for installation.

#### **Content:**

- » Aluminum-/steel structure/metal roof
- » Static calculations of the racking
- » Racking system for the trapezoidal roof
- » Trapezoidal sheet metal colours:











brick red

anthracite

e light grey

white


RAL colours

## **REQUIRED ON SITE**

### (to be provided by customer)

- » Static calculation of the foundation
- » Equipment to unload our delivery trucks, competent and qualified installation/assembly team, concrete foundation incl. anchoring and installation of the same, modules, inverters, electrical installation, grid connection, permits. (On request, we will be happy to name installation companies in your area).









### **HOW AND WHY?**

In the following flow chart you will find the chronological steps for ordering a carport system.



By receiving your check list, we get the most important information about your project; location, type of solar panel and **layout**. With this information we can determine the snow and wind loads according to the local building codes and geographical conditions.

We advise you on the possible carport solutions for your project, taking into account the project-specific loads. We also offer suggestions for optimization and/or possible additional components. Based on this, you receive a budgetary offer (excluding foundation details).

Especially for larger carports (> 100 kWp), information about the residual bearing capacity and tensile strength of the soil is required in order to determine the most economical foundation method for you. Subsequently, the final price is calculated and we provide an estimated delivery time.

The commercial and technical negotiations have been completed. After we received your order, the exact delivery time will be determined. Only after we received your official order can we book the production slots for your system.

Once the design is finalized and all commercial and technical conditions are clarified, we will provide detailed drawings of your specific system. Earlier on, we only suppled **sample drawings**.

Please note that the above mentioned scope does not include the supply of a binding yield calculation!





Thank you for your interest in our systems. In order to provide you with a precise offer, we ask you to fill out the check list as detailed and precise as possible.

CONTACT	
Company nan	e
Last name, fir	t name
Street	
Postal code	City
Country	
Phone	
E-Mail	
LOCATION CO	ONSTRUCTION FIELD
	ONSTRUCTION FIELD
Street	City
Street Postal code	
Street  Postal code  Country	City
Street  Postal code  Country  Height above	City
Street  Postal code  Country  Height above  MANDATORY  » Google Ea	City

This information is crucial for us to provide a quote!

MODULE LAYOUT	
O Vertical O Horizontal	Inclination (We recommend 5 - 15°)
Modules on top of each other (pcs.)	Modules side by side (pcs.)

CARPORT OPTIONS  □ C1S One-sided sun protection □ C1R One-sided rain protection □ C2S Double-sided sun protection □ C2R Double-sided rain protection □ C2YS Y-Version, double-sided sun protection □ C2YR Y-Version, double-sided rain protection			
No. of parking spots  Ground clearance H (m)			
Axis A (m) (max. 7,5m with Show load zone 2)  A (max. 7,5 m)			

PARKING	
□ Vertical C1	999999
☐ Vertical C2/C2Y	



## **CHECKLIST**

SUPPLY LINES	EXPLOSIVE ORDNANCE AND REMNANTS OF WAR
Are there any supply lines on the project site? If available, please provide plans with dimensions:  □ Electricity □ Water □ Gas □ Phone □ Drainage	We assume that there are no unexploded ordnance in the soil. Especially for industrial areas and old airports we recommend an inquiry at the aerial photograph database (www.luftbilddatenbank.de). In case of an order we require a written confirmation.
☐ There are no supply lines	PLEASE NOTE THE FOLLOWING FOR THE INVESTIGATION:
SITE SURFACE	» At the beginning of the soil investigation, one of your
□ Pavers □ Concrete □ Asphalt	team members should point out the project area to our geotechnical engineer, to ensure that the testing is conducted at the correct location and damage to supply lines can be avoided.
SOIL PROPERTIES	» If a geological survey of the project site has already been carried out, or specific features of the subsoil are known, these should be communicated to us in advance.
Does the subsoil consist in whole or in part of:  ☐ Fill ☐ Contaminated soil	The results of the subsoil investigation help us in assessing the project site.
Have any measures already been taken/are planned for soil improvement (e.g. soil replacement, geogrid/fleece)?	Changes made to the subsoil after the investigation (e.g. excavations, backfill, soil rearrangements, etc.) may require a new investigation, resulting in additional cost for the client.
Additional information:	The soil investigation can only be carried out if we have received the completely filled out and signed checklist as well as the site plans.
This data sheet only contains information for SL Rack ties. The content of this document depends on the lo requirements. Note: We collect personal data. Pleaso website at <b>www.sl-rack.de</b>	
The General Terms and Conditions of Sale and Deli apply. They are available at www.sl-rack.de	very of SL Rack GmbH in their current version shall
Place Date	Signature

SL Rack

**Website** 







SL Rack **YouTube** 



Contact us for an offer:



Münchener Straße 1 83527 Haag i. OB E-Mail: sales@sl-rack.com

Phone: +49 8072 3767-0

SL Rack **Onlineshop** 



www.sl-rack.com

Subject to technical changes and misprints. Version 05/2023 V8